



ORBITER SLING™ SPECIFICATION

MOBILE RFID WEARABLE READER FOR RACE TIMING.

Mobile Performance with Extreme Tag Read Power, 3X a handheld, New WI-FI for real time results.

The SLING allows ultimate mobility with advanced RF communications. Superior performance than RFID handhelds with 24 volts of power versus 8 volts with a handheld. See results in real time on a tablet or laptop via WI-FI.

Excellent form factor for normally difficult to time Triathlon Races and made easy timing of 5K races. Not mats or Overhead structures.

Utilizing the same readers as the Orbiter SPIRE, we modified the core RFID embedded radio software from the ground up to enhance speed, more accurate read rates and provide consistent performance in harsh RF environments. The difference between the SLING 20 ft of range and the SPIRE 40 feet of range is antenna size using a bib tag.

The SLING still has the same powerful internal RFID reader as the Orbiter SPIRE. Our system is designed for constant up and down wireless communication. We are experts in wireless data communications as our engineers have worked together since the mid '90's for Civilian, Aerospace, and Military projects. True rocket scientists. Plus, we have many successful deployed RFID applications worldwide for Fortune companies, Governments, Agriculture, Events, Resorts, Automotive and Oil company applications. If you have read about a successfully deployed RFID application, chances our team has done similar.

No other mobile device has the increased voltage the Orbiter SLING for robust tag detections in a crowded environment. No RFID handheld has the extended 20 ft. RFID tag to communication range. For races of 500 people or less, detect tags placed anywhere on the body. For large scale global deployments, use the SLING with a SPIRE to time any size race.



SLING PHYSICAL CHARACTERISTICS

Dimensions: 22" (H) x 15" (L) x 6" (W).
 55.8 cm (L) x 38.1 cm (L) x 12.24 (W)
Weight: 13.4 lbs (6.08 kg) including batteries.
Housing Material: Anti Static Foam in a Rugged sling bag, plastics.
Visual Status Indicators: Multi Color LED's for power condition and application status.
Mounting: Mobile placement with high quality in-line skate wheels with bearings for smooth roll on surface.

CONNECTIVITY

Communications: Proprietary RF communications to application layer. 10/100 Base T Ethernet (RJ45) w POE support, USB Client (USB Type B), USB Hoist Port (Type A).
General Purpose I/O 2 input, 32 outputs, optically isolated (Terminal Block).
Power Supply: POE, POE+ or + 24V DC (UL Approved), 120 and 220 AC Marine Plug.
Antenna Ports: Standard Multi Ports connected to Orbiter Phased Detect antenna. Optional 4 and 8 port models available for connecting customer selected antennas.

ENVIRONMENTAL

Operating Temp – Min -23 degrees F (-30.5) Vancouver, BC, Canada, Nov 30, 2015.
 High 131 degrees F, 55 degrees C, Death Valley, CA, July 2015.
Humidity 5-95% non-condensing
Shock and Vibration: MIL-STD-810G

REGULATORY COMPLIANCE

Safety UL 60950-01, UL 2043, IEC 60950-1, EN 90950-1
RF/EMI/EMC FCC Part 15, RSS 210, EN 302 208, ICES-003 Class B, EN 301 489-1/3, MIC school broadcast, regional pre-approval.
SAR/MPE FCC 47CFR2: OET Bulletin 65; EN 50364
Other: ROHS, WEEE

HARDWARE, OS AND FIRMWARE MANAGEMENT

Memory Flash 512 MP, DRAM 256 MP
Operating System Linux
Application Code: Java
Firmware Upgrade Web-based and remote firmware upgrade capabilities
Management Protocols RM 1.0.1 (with XML over HTTP/HTTPS and SNMP and NTP
Network Stack IPv4 and Ipv6
Security Transport Layer Security Ver 1.2 FIPS 140
Air Protocols EPCglobal UHF Class 1 Gen2 ISO 18000 BC
Frequency Band Global Reader 902 MHz – 928 MHz (Maximum, supports countries that use a part of this band) 865 MHz – 869 MHz., 2.4 GHz International Accepted WI-FI band, and Country specific accepted data cellular band.
Transmit Power Output 10 dBm to +31.5 dB, (POE+ 24 volt External DC) +10dBm to +30.0 dBm (POE).
Max Receive Sensitivity -82 dBm
IP Addressing Static and Dynamic
HOST Interface Protocol ORP and LLRP
API Supported Host Applications – Java EDK and Net C, Embedded Applications Java SDK
Warranty 1 year all parts and labor

RECOMMENDED SERVICES

Annual Service and Support includes all parts and labor warranty extension plus automatic software upgrades for 18% of sale price annually.

Advanced Services

RFID design and world wide deployment including IC tag & antenna design, reader build (LF, HF, NFC, UHF, Microwave, IR), application software for local and cloud scaled for super computers. Global reach with in country technicians to service your needs.

